

LOCK & DAM CAPABILITIES



Metric Product Starting at M20

# LOCK & DAM PRODUCTS AND SPECIFICATIONS

Dyson creates products for virtually all parts of locks and dams including tainter gate, flood gate and bulkhead gates.

### Product line includes:

- Custom Forgings Turnbuckles Clevises
- Pins and Shafts
- Bearings and Hubs Eyebolts/Eyebars
- Heavy Hex Bolts
- Heavy Hex Nuts
- Spanner Nuts
- Lift Stems
- Diagonals

Threads

Misc.

and UNJ

• Class 2, 3 & 5

Rolled or Ground

• Standard, Metric,

• Lockwire Holes

Special Machine

ACME and Specials

Link Assemblies

- Jam Nuts Connecting Pins
- Latch Pin Assembly

- - Rolled Threads Available

Sleeve Nuts

Standard, Butress.

Threads Available

Square, Acme & Custom

- **Specifications** • UNC, 8UN, UNF, UNR Carbon Alloy Stainless Chaser, Single Point, • Nitronic Monel K500 Monel Inconel Titanium Self Locking Fasteners Brass Bronze Secondary Machining Copper Coatings Zinc Cadmium Phosphate Ceramic IVD Chrome Copper • SAE-J995 (grades 2, 5 & 8) Flash Tool Steels Black Oxide • MIL-C-87115

See Products and Specifications for other Dyson Industries

Wind Power	Nuclear	Mining	Bridges	Military	Forklift Arms
				Pr Prsen	

PRODUCTS					
Bolts	Diameters	Lengths			
Hex (regular & heavy)	1/2" thru 8"	up to 60'			
Square (regular & heavy)	1/2" thru 8"	up to 60'			
Liner/Taper (all styles)	1/2" thru 8"	up to 60'			
T-Head	1" thru 8"	up to 60'			
Eyebolts/Lifting Eyes	1" thru 8"	up to 60'			
U-Bolts	1" thru 6"	up to 30"			
Screws (Fitted Bolts)	Diameters	Lengths			
Hex Cap (regular & heavy)	1/2" thru 8"	up to 60'			
Socket Head Cap	1/2" thru 8"	up to 60'			
Slotted Head Flat	1/2" thru 8"	up to 60'			
Socket Set (all types)	1/2" thru 8"	up to 60'			
Flange (hex, square, and 12 pt.)	1/2" thru 8"	up to 60'			
Studs and Rods	Diameters	Lengths			
Continuous Threaded (TFL)	1/2" thru 6"	up to 60'			
Double End/Single End	1/2" thru 8"	up to 60'			
Upset Tie-Rods	3/4" thru 5"	up to 60'			
Nuts	Diameters				
D-LOC <sup>®</sup> (sealing lock nut/full & jam)	1" thru 6"				
Various Sealing Systems	1/2" thru 3"				
Hex (full & jam/regular & heavy)	1/2" thru 12"				
Square (regular & heay)	1/2" thru 18"				
Capnuts (hex or socket)	1/2" thru 12"				
Coupling RH/RH (all types)	3/4" thru 12"				
Sleeve RH/LH (all types)	3/4" thru 12"				
<b>Custom Forgings</b>	Diameters	10,000 lbs.			
Forged Bar	2" thru 20"	Per Part			
Forged Plate	2" thru 20"				
Shafting	2" thru 20"				

Critical Application and Alternate Sizes by Request



Domestic Fasteners and Forgings Since 1884

The Dyson Corporation 53 Freedom Road Painesville, Ohio 44077 Phone: 440-946-3500

Toll Free: 1-800-680-3600 Fax: 440-352-2700 salesquotes@dysoncorp.com www.dysoncorp.com

 Bridge Pins • Recessed Pin Nuts • Gudgeon Links and Pins

- Caps
- Achorage Pins
- Forged Plate
- Strut Pins
  - **SPECIFICATIONS Materials**

## **Common Product**

- ASTM-A193 (gr B7, B16, SS) • ASTM-A194 (gr 2, 2H,7 & SS) ASTM-A307 (grades A & B) • ASTM-A320 (gr L7 & L43) • ASTM-A325 • ASTM-A354 (gr BC & BD) • ASTM-A449 • ASTM-A490 (types 1 & 3) ASTM-A563 (gr A-C, DH & DH3) • ASTM-A568 (8.8, 10.9 & 12.9) • ASTM-A574 • ASTM-A615 ASTM-A668 (all classes) ASTM-A709 • ASTM-A722 • SAE-J429 (grades 2, 5 & 8)

- DIN Standards
  - ISO Standards
- Custom Requirements Available

- Finishes • Tight Tolerance Requirements
- Custom Testina and Inspection
- Special Assembly and Packaging
- Restricted Carbon Content of .35% Max Available
- NDT Testing (UT, MT & Radiograph • Prolongation Testing